



PRODUCT: 5909 ETCH-FILL ONE STEP GRAY PRIMER 340 g / 12 oz

SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED FOR ABI / Autobody Brands International
a Division of IAMG / International Autobody Marketing Group 1505
North Hayden Road, Suite 111
Scottsdale, AZ 85257
INFORMATION PHONE: 1-87-REFINISH
24-Hour Medical Emergency CHEMTREC Phone: (800) 424-9300
PRODUCT NAME..... 5909 ETCH-FILL ONE STEP GRAY PRIMER 340 g/ 12 oz
CHEMICAL FAMILY..... MODIFIED NITROCELLULOSE COATING.
MOLECULAR WEIGHT..... NOT APPLICABLE.
CHEMICAL FORMULA..... MIXTURE.
TRADE NAMES & SYNONYMS..... NOT APPLICABLE.
RECOMMENDED PRODUCT USES..... COATING.
CAS #..... NOT APPLICABLE..

SECTION 02: HAZARDS IDENTIFICATION



HAZARD CLASSIFICATION..... DANGER.
SIGNAL WORD..... Danger.
HAZARD STATEMENTS H223 FLAMMABLE AEROSOL. H229 PRESSURIZED CONTAINER: MAY BURST IF HEATED. H302+H332 HARMFUL IF SWALLOWED OR INHALED. H315 CAUSES SKIN IRRITATION. H320 CAUSES EYE IRRITATION.
PRECAUTIONARY STATEMENTS..... P101 IF MEDICAL ADVICE IS NEEDED, HAVE PRODUCT CONTAINER OR LABEL AT HAND. P102 KEEP OUT OF REACH OF CHILDREN. P103 READ LABEL BEFORE USE.
OTHER HAZARDS..... No additional information available.

SECTION 03: COMPOSITION/INFORMATION INGREDIENTS

Table with 3 columns: HAZARDOUS INGREDIENTS, CAS #, WT. %. Lists ingredients like ACETONE, DIBUTYL PHTHALATE, ETHYLBENZENE, etc.

PRODUCT: 5909 ETCH-FILL ONE STEP GRAY PRIMER 340 g / 12 ozz**SECTION 04: FIRST AID MEASURES**

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

SECTION 05: FIRE FIGHTING MEASURES

FLAMMABILITY..... EXTREMELY FLAMMABLE.
 IF YES, UNDER WHICH CONDITIONS?..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.
 SPECIAL PROCEDURES..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.

EXPLOSION DATA
 SENSITIVITY TO STATIC DISCHARGE. NOT APPLICABLE.
 SENSITIVITY TO IMPACT..... NOT APPLICABLE.

EXTINGUISHING MEDIA..... WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

HAZARDOUS COMBUSTION PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.

AEROSOL FLAME PROJECTION CLASSIFIED AS:..... >15cm BUT <100cm.
 FLASHBACK..... NONE.

SECTION 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL..... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

SECTION 07: HANDLING AND STORAGE

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.
 ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).

HANDLING PROCEDURES AND STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.
 EQUIPMENT
 SYNERGISTIC MATERIALS..... NONE KNOWN.

SECTION 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
ACETONE	750 ppm					
DIBUTYL PHTHALATE	5mg/cu.m.					
ETHYLBENZENE	100 ppm					
ISOBUTANE	1000 ppm					
ISOPROPANOL	400 ppm					
METHANOL	200 ppm					
METHYL ETHYL KETONE	200 ppm					
METHYL ISOBUTYL KETONE	50 ppm					
NITROCELLULOSE	NOT AVAILABLE					
PROPANE	1000 ppm					
TALC (MAGNESIUM SILICATE HYDRATE)	2 mg/m ³					
TITANIUM DIOXIDE	N/A					
XYLENE	100 ppm					
GLOVES/ TYPE.....	NONE REQUIRED FOR NORMAL APPLICATION OF AEROSOL PRODUCTS WHERE MINIMAL SKIN CONTACT IS EXPECTED.					
RESPIRATORY/TYPE.....	IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.					

PRODUCT: 5909 ETCH-FILL ONE STEP GRAY PRIMER 340 g / 12 oz**SECTION 08: EXPOSURE CONTROLS/PERSONAL PROTECTION**

EYE/TYPE..... SAFETY GLASSES.
 FOOTWEAR/TYPE..... NOT NORMALLY REQUIRED.
 OTHER/TYPE..... NOT REQUIRED.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... AEROSOL.
 APPEARANCE..... GREY.
 ODOR..... KETONE.
 ODOR THRESHOLD..... NOT AVAILABLE.
 pH..... NOT APPLICABLE.
 FREEZING POINT: (°C)..... NOT AVAILABLE.
 BOILING POINT (°C)(CONC)..... 57-143.
 FLASH POINT (C), TAG CLOSED CUP..... LOWEST KNOWN VALUE IS ACETONE @ -18C.
 EVAPORATION RATE..... GREATER THAN 1.
 n-BUTYL ACETATE = 1
 UPPER FLAMMABLE LIMIT..... 12.6.
 (% BY VOLUME)
 LOWER FLAMMABLE LIMIT..... 1.0.
 (% BY VOLUME)
 VAPOUR PRESSURE(PSIG)-AEROSOL..... 55-65.
 @ 20 C
 VAPOUR DENSITY (AIR=1)..... GREATER THAN 1.
 (BY WEIGHT)
 SPECIFIC GRAVITY (AEROSOL)..... 0.77-0.81.
 SPECIFIC GRAVITY (LIQUID)..... 0.90-0.94.
 SOLUBILITY IN WATER g/L (20°C)..... NOT AVAILABLE.
 COEFFICIENT OF WATER/OIL DIST..... NOT AVAILABLE.
 AUTO IGNITION TEMPERATURE (°C)..... 399-527.
 AEROSOL PERCENT VOLATILE..... 86-87.

SECTION 10: STABILITY AND REACTIVITY

HAZARDOUS PRODUCTS OF
 DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION
 IS INCOMPLETE.
 CHEMICAL STABILITY:
 YES..... UNDER NORMAL CONDITIONS.
 NO, WHICH CONDITIONS?..... NOT APPLICABLE.
 COMPATIBILITY WITH OTHER
 SUBSTANCES:
 NO, WHICH ONES?..... STRONG OXIDIZING AGENTS.
 REACTIVITY CONDITIONS?..... NOT APPLICABLE.
 HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
ACETONE	>16,000 ppm (4 hr) INHAL - RAT	>9750 mg/kg ORAL - RAT
DIBUTYL PHTHALATE	7.9 mg/m3 INHAL - RAT	8 g/kg ORAL - RAT
ETHYLBENZENE	0.05-0.15.	
ETHYLBENZENE	100 ppm	
ROUTE OF ENTRY: INHALATION.....	INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXIAN.	
INGESTION.....	MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS. METHANOL MAY CAUSE BLINDNESS AND DEATH.	
EYE CONTACT.....	MAY CAUSE IRRITATION.	
SKIN CONTACT.....	MAY CAUSE IRRITATION. METHANOL.	
SKIN ABSORPTION.....	NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.	
EFFECTS OF ACUTE EXPOSURE.....	DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES.	
EFFECTS OF CHRONIC EXPOSURE.....	SOLVENTS MAY CAUSE DEFATTING DERMATITIS	
IRRITANCY OF MATERIAL.....	SKIN/EYE IRRITANT.	

PRODUCT: 5909 ETCH-FILL ONE STEP GRAY PRIMER 340 g / 12 oz**SECTION 11: TOXICOLOGICAL INFORMATION**

CARCINOGENICITY/MUTAGENICITY.....	XYLENE - THIS PRODUCT CONTAINS ETHYLBENZENE (ETHYLBENZENE IS IN XYLENE). ETHYLBENZENE HAS BEEN SHOWN TO CAUSE CANCER IN LABORATORY ANIMALS. TOXICITY TESTS CARRIED OUT FOR CHRONIC EFFECTS AND MUTAGENICITY HAVE BEEN NEGATIVE. THE RELEVANCE OF THIS FINDING TO HUMANS IS UNCERTAIN. IARC HAS CLASSIFIED ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN.
TERATOGENICITY.....	NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE ANTICIPATED.
REPRODUCTIVE EFFECTS.....	XYLENE - HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT LEVELS TOXIC TO THE MOTHER, AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.
SENSITIZING CAPABILITY OF MATERIAL.	UNKNOWN.

SECTION 12: ECOLOGICAL CONSIDERATIONS

ENVIRONMENTAL..... NOT AVAILABLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL..... DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

SECTION 14: TRANSPORTATION INFORMATION

T.D.G. CLASSIFICATION..... CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1 (6.1)).
D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.

SECTION 15: REGULATORY INFORMATION

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION..... A,B5,D1B,D2A,D2B.
CNFC SECTION 3.3.5..... LEVEL 2.
CEPA (Canadian Environmental Protection Act) ... ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.

U.S. REGULATIONS:

HMIS RATING HEALTH..... 2 MODERATE HAZARD.
HMIS RATING FLAMMABILITY..... 4 SEVERE HAZARD.
HMIS RATING REACTIVITY..... 1 SLIGHT HAZARD.
HMIS RATING PERSONAL PROTECTION.. B.
NFPA CODE 30B..... LEVEL 2.
SARA 313 INFORMATION:..... THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

. CAS #:	CHEMICAL NAME:
. *1330-20-7	XYLENE
. *100-41-4	ETHYL BENZENE
. *67-56-1	METHANOL

CALIFORNIA PROPOSITION 65:..... THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:

. WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.	. CAS #:	CHEMICAL NAME:
	. *100-41-4	ETHYL BENZENE IN XYLENE

TSCA (Toxic Substances Control Act)..... ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.
V.O.C.(M.I.R.)..... COMPLIES WITH PRIMER COATING CATEGORY OF <1.2 g OZONE / g PRODUCT.

SECTION 16: OTHER INFORMATION

NOTICE FROM K-G SPRAY- PAK INC THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY K-G SPRAY PAK INC. FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. K-G SPRAY PAK INC. ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES

PRODUCT: 5909 ETCH-FILL ONE STEP GRAY PRIMER 340 g / 12 oz**SECTION 16: OTHER INFORMATION**

NOTICE FROM Autobody Brands International THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY Autobody Brands International FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. Autobody Brands International ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

PREPARED BY..... Regulatory Affairs

PREPARATION DATE June 9, 2015