

* 1 Identification

- **Product identifier**
- **Trade name:** *IM8311 White Basecoat*
- **Article number:** *IM8311*
- **Application of the substance / the mixture** *Coating*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Manufactured for: IAMG International Autobody Marketing Group, 1505 North Hayden Road, Ste.111, Scottsdale, AZ 85257
Information phone : 480.451.4451
- **Information department:** *1-87-REFINISH*
- **Emergency telephone number:** *CHEMTREC 1-800-424-9300*

* 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 1 H360 May damage fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*

Trade name: IM8311 White Basecoat

(Contd. of page 1)

Hazard-determining components of labeling:

benzyl butyl phthalate
bis(1,2,2,6,6-Pentamethyl-4-piperidiny) sebacate

Hazard statements

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.

Precautionary statements


P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)



(Contd. on page 3)
USA

Trade name: IM8311 White Basecoat

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:**

Mixture: consisting of the following components.

Weight percentages

- **Dangerous components:**

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene	13-30%
67-64-1 acetone	13-30%
1330-20-7 xylene	≥7-<10%
110-43-0 heptan-2-one	≥7-<10%
763-69-9 ethyl 3-ethoxypropionate	1.5-5%
85-68-7 benzyl butyl phthalate	1.5-5%
41556-26-7 bis(1,2,2,6,6-Pentamethyl-4-piperidiny)l sebacate	≥0.1-<1%
108-88-3 toluene	≥0.1-≤1%

* 4 First-aid measures

- **Description of first aid measures**

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

* 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture** No further relevant information available.

- **Advice for firefighters**

- **Protective equipment:** No special measures required.

USA

(Contd. on page 4)

Trade name: IM8311 White Basecoat

(Contd. of page 3)

* 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

13463-67-7 titanium dioxide	30 mg/m ³
67-64-1 acetone	200 ppm
1330-20-7 xylene	130 ppm
110-43-0 heptan-2-one	150 ppm
763-69-9 ethyl 3-ethoxypropionate	1.6 ppm
85-68-7 benzyl butyl phthalate	15 mg/m ³
108-88-3 toluene	67 ppm

· **PAC-2:**

13463-67-7 titanium dioxide	330 mg/m ³
67-64-1 acetone	3200* ppm
1330-20-7 xylene	920* ppm
110-43-0 heptan-2-one	670 ppm
763-69-9 ethyl 3-ethoxypropionate	18 ppm
85-68-7 benzyl butyl phthalate	77 mg/m ³
108-88-3 toluene	560 ppm

· **PAC-3:**

13463-67-7 titanium dioxide	2,000 mg/m ³
67-64-1 acetone	5700* ppm
1330-20-7 xylene	2500* ppm
110-43-0 heptan-2-one	4000* ppm
763-69-9 ethyl 3-ethoxypropionate	110 ppm
85-68-7 benzyl butyl phthalate	460 mg/m ³
108-88-3 toluene	3700* ppm

* 7 Handling and storage

· **Handling:**

· **Precautions for safe handling** No special measures required.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 5)
USA

Trade name: IM8311 White Basecoat

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

*** 8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

BEI

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm

Long-term value: 434 mg/m³, 100 ppm

BEI

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm

BEI

- **Ingredients with biological limit values:**

67-64-1 acetone

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 6)

USA

Trade name: IM8311 White Basecoat

(Contd. of page 5)

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)
USA

Trade name: IM8311 White Basecoat

(Contd. of page 6)

· **Eye protection:**



Tightly sealed goggles

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Liquid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

55.8-56.6 °C

· **Flash point:**

-18 °C

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

465 °C

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

· **Lower:**

2.6 Vol %

· **Upper:**

13 Vol %

· **Vapor pressure at 20 °C:**

233 hPa

· **Density at 20 °C:**

1.15254 g/cm³

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**

· **Water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** *Not determined.*

· **Viscosity:**

· **Dynamic:**

Not determined.

· **Kinematic:**

Not determined.

· **Solvent content:**

· **Organic solvents:**

56.6 %

(Contd. on page 8)

USA

Trade name: IM8311 White Basecoat

(Contd. of page 7)

VOC content: 19.84 %
395.0 g/l / 3.30 lb/gl

Solids content: 43.4 %

Other information No further relevant information available.

*10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
 - 1330-20-7 xylene**
 - Oral LD50 4,300 mg/kg (rat)
 - Dermal LD50 2,000 mg/kg (rabbit)
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**

13463-67-7 titanium dioxide	2B
1330-20-7 xylene	3
85-68-7 benzyl butyl phthalate	3
108-88-3 toluene	3
- **NTP (National Toxicology Program)**

None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

*12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 9)
USA

Trade name: IM8311 White Basecoat

(Contd. of page 8)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

*14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR** 1263 Paint, special provision 640D
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**



- **Class** 3 Flammable liquids
- **Label** 3
- **ADR, IMDG, IATA**



- **Class** 3 Flammable liquids

(Contd. on page 10)
USA

Trade name: IM8311 White Basecoat

(Contd. of page 9)

· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

*15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredient is listed.
- **Section 313 (Specific toxic chemical listings):**
1330-20-7 xylene
108-88-3 toluene
- **TSCA (Toxic Substances Control Act):**
13463-67-7 titanium dioxide
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene
67-64-1 acetone
1330-20-7 xylene
110-43-0 heptan-2-one
9004-36-8 Cellulose Acetate Butyrate
763-69-9 ethyl 3-ethoxypropionate
85-68-7 benzyl butyl phthalate

(Contd. on page 11)

USA

Trade name: IM8311 White Basecoat

(Contd. of page 10)

- 41556-26-7 bis(1,2,2,6,6-Pentamethyl-4-piperidiny) sebacate
- 61791-55-7 Amines, N-tallow alkyltrimethylenedi-
- 108-88-3 toluene
- 82919-37-7 Methyl (1,2,2,6,6,- pentamethyl-4-piperidiny) sebacate
- 106-79-6 Dimethyl sebacate(Impurity)
- 2403-89-6 4-Piperidinol, 1,2,2,6,6 pentamethyl- (Impurity)

· **Proposition 65**

· **Chemicals known to cause cancer:**

- 13463-67-7 titanium dioxide
- 1330-20-7 xylene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

- 85-68-7 benzyl butyl phthalate
- 108-88-3 toluene

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

- 67-64-1 acetone I
- 1330-20-7 xylene I
- 85-68-7 benzyl butyl phthalate C
- 108-88-3 toluene II

· **TLV (Threshold Limit Value established by ACGIH)**

- 13463-67-7 titanium dioxide A4
- 67-64-1 acetone A4
- 1330-20-7 xylene A4
- 108-88-3 toluene A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

- 13463-67-7 titanium dioxide

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

- benzyl butyl phthalate
- bis(1,2,2,6,6-Pentamethyl-4-piperidiny) sebacate

(Contd. on page 12)

USA

Trade name: IM8311 White Basecoat

(Contd. of page 11)

· **Hazard statements**

- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H360 May damage fertility or the unborn child.

· **Precautionary statements**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

***16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** 1-480-451-4451 Lloyd Fields

· **Date of preparation / last revision** 04/09/2018 / 8

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 13)

Printing date 04/09/2018

Reviewed on 04/05/2016

Trade name: IM8311 White Basecoat

(Contd. of page 12)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 1: Reproductive toxicity – Category 1

*** Data compared to the previous version altered.**

USA