

5 STAR ADVANTAGE® AUTOBODY PRODUCTS

TECHNICAL DATA INFORMATION

DATED: MAY 2020

PRODUCT NUMBER

#3521 Lacquer Spray Paint – Gloss Black (Aerosol)	12oz.	12/cs
#3522 Lacquer Spray Paint – Flat Black (Aerosol)	12oz.	12/cs
#3523 Lacquer Spray Paint – Semi-Gloss Black (Aerosol)	12oz.	12/cs

DESCRIPTION:

A fast drying lacquer spray paint that provides durable indoor and outdoor protection. Resistant to the effects of weather and many chemicals. Resists abrasion and heat (250F). **Bare surfaces or rusted metal surfaces should first be primed with primer to ensure proper adhesion.**

SUGGESTED USES:

Metal, Wood, Furniture, Toys, Boats, Bikes.

Quick dry, Close-up spray 8-10", Reduces overspray and sag.

DIRECTIONS:

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. Do not stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. **DO NOT incinerate or compact.**

Dry Time*:

To touch 5 minutes

To recoat 20 minutes

*At 72° F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*:

High Gloss, >80

Flat, <15

*as measured on a 60° gloss meter

PROPERTIES:

Flammability "Extremely Flammable"
Specific Gravity 0.86
Solids Content Glosses: ~12% Flats: ~13%
MIR value Glosses: ~1.25, cannot exceed 1.40
Clear: ~1.43, cannot exceed 1.50
HAPs content Glosses: ~10% Clear: ~27%
Storage Temperature 40-100F
Application Temperature 50-90F
Durability Good
Abrasion Resistance Good
Gasoline Resistance No
Heat Resistance 250 F
Resin System Lacquer
Shelf life Guaranteed for 2 years

Packaging:

Cans per case 12/cs
Shipping weight per case 15 lbs.
Container 16 fluid ounce can
Label weight 12 ounces (340 grams)
Shipping Classification Consumer Commodity
ORM-D, UN 1950
Hazard Class 2.1

SAFETY INFORMATION - FOR INDUSTRY USE ONLY

DANGER Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

Prevention: Pressurized container: do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/clothing. Wear protective gloves/clothing/glasses. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources. Response: In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have product label at hand. IF IN EYES: Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention. IF SWALLOWED: Rinse mouth with water. Do not induce vomiting. IF INHALED: Remove to fresh air. IF ON SKIN: Wash thoroughly with water. Remove all contaminated clothing. Storage: Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Disposal: Dispose of product in accordance with local/regional/national/international regulations. Additional Precaution Statements: Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. In cases where short and/or long term overexposure conditions exist, a charcoal filter

respirator should be worn. Follow respirator manufacturer's directions for use.

KEEP OUT OF REACH OF CHILDREN.

WARNING: Cancer and Reproductive Harm

www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et Harm Reproductive

www.P65Warnings.ca.gov

ADVERTENCIA: Cáncer y Daños Reproductivos

www.P65Warnings.ca.gov

For Chemical Emergencies/Pour les urgences chimiques

Para Emergencias Químicas

Contact CHEMTREC (day or night) at 1-800-424-9300

www.5starxtreme.com / www.advantagerefinish.com

Manufactured in U.S.A (Manufactured for - ABI/Autobody Brands
International a division of IAMG/International Autobody Marketing Group)

1505 N. Hayden Rd. Ste. 111, Scottsdale, AZ 85257

1-87-REFINISH

Distributed in Canada by: ABI (Autobody Brands International)

A division of IAMG/International Autobody Marketing Group

1368 United Blvd., Unit 102, Coquitlam, BC V3K 6Y2, Canada