

5 STAR XTREME AUTOBODY PRODUCTS
TECHNICAL DATA INFORMATION
DATED: DECEMBER 2013

PRODUCT NUMBER

#5917 – Premium Gloss Black Lacquer (Aerosol 12.25 oz.)

DESCRIPTION:

CAP INDICATES COLOR OF CONTENTS – GLOSS BLACK

#5917 resists fading, chipping, stains, weather and corrosion. Dry to the touch in 15 mins, can be handled in 1 hour.

DIRECTIONS:

PREPARE SURFACE. Remove rust, scale, dirt, grease, etc. Scuff-sand glossy or hard surfaces. Etch galvanized metal. Wash with a mild detergent, rinse well and dry with clean cloth. Mask of areas to be protected from overspray. PRIME exposed bare metal, with 5 STAR XTREME Primer - (1) Use at room temperature (70°F) for best results. Do not paint on days when humidity is high. (2) Shake can for one full minute after mixing ball rattles. Repeat for 10 seconds after each minute of use. Clear has no mixing ball. (3) TO SPRAY, hold can 6-10 inches from surface. Use steady, even strokes, keeping can parallel to the surface throughout the stroke. Apply a light mist coat, followed by a full coat. Handle carefully for first few hours. Recoat within 1 hour or wait 5 days for through dry. (4) If spray button becomes clogged, pull off and clean. DO NOT stick pins or wire into can opening. Replace spray button firmly with valve opening pointed away from you. (5) To clean valve after use, invert can and spray until only clear gas comes out. Discard empty can in trash pick-up. Do not burn, incinerate, or place in home garbage compactor. The EZ TOUCH™ FANSPRAY® valve requires 50% less finger pressure than a standard valve. Allows greater coverage with less overspray, and manipulates like a professional spray gun.

CAUTIONS:

CAUTIONS CONTAINS ACETATES AND KETONES. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. FIRST AID: In case of eye contact, flush thoroughly

with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

SEE MSDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION.

ABI – Autobody Brands International a division of IAMG – International Autobody Marketing Group. www.5starxtreme.com - Scottsdale, AZ 85257